



# COMMERCIAL LAUNDRY SYSTEMS

TITAN-C



## Washer

		Non-Heater	
<b>CYLINDER</b>			
Drum Volume	cu.ft (l)	5.2 (147)	
Diameter	in. (mm)	24 (610.8)	
Depth	in. (mm)	20.4 (518.1)	
Capacity	lb (kg)	33 (15)	
<b>DIMENSIONS</b>			
Product (WxHxD)	in.(mm)	29 (737) x 40.8 (1,036) x 32 (814)	
With Door Opening	in.(mm)	53 (1,370)	
Carton (WxHxD)	in.(mm)	31 (788) x 44.3 (1,125) x 33.3 (846)	
Weight (Product/Carton)	lb (kg)	221.8 (100.6) / 248 (112.5)	
<b>SPEED</b>			
Wash	RPM	46	
Extract (High Speed)	RPM	980	
G-force	G	327	
<b>ENERGY</b>			
Electric Ratings	V/Hz/A	120/60/5	
<b>WATER USAGE</b>			
Water Consumption	gal (l)	17.8 (67.6)	
<b>NOISE &amp; CYCLE TIME</b>			
Noise Level (Sound Power)	dB	Lower than 62	
Program Duration in Minutes (Default)	min	35	
<b>SYSTEM &amp; CONTROL</b>			
Inverter Direct Drive Motor		0	
Intelligent Electronics Controls		0	
Heating System	W	1,000 (Only for Tub Clean)	
Compartment Dispenser		3 Compartment Dispenser	
Drain System		Gravity Drain	
Pricing Program		Special Vended Price	
Emergency Stop Button		0 (OPL Only)	
Auto Dosing Interface		0	
Damper		4 Friction Fampers (ASK 80N)	
<b>PROGRAMS</b>			
Program List		Hot	
		Warm	
		Cold	
		Delicates	
		Add Super Wash (Card & OPL) / CUSTOM PGM (OPL)	
<b>EXTERNAL FINISH</b>			
Drum		Stainless Steel Drum	
Top Plate		Porcelain (Single)	
Transparent Glass Window Door		0	
Colors		Platinum	
Cabinet		Painted Steel	
Cabinet Cover		Painted Steel	
Control Panel		Painted Steel	
Panel Frame		Painted Steel	
Panel Frame Lower		Painted Steel	
Window Display		Silk Screen	
Window Display Sheet		Aluminum	
<b>CIRCUIT PROTECTION</b>			
PCB Fuse - Main Control Board	amps	12	
PCB Fuse - Filter Assembly	amps	15	
<b>Non-Heater</b>			
	Coin	Card	OPL
Single	F10C7FD4	F10C7FD7	F10C7FD3
Stack	-	-	-

- \* Dimensions and weights are approximate.
- \* Design, features and specifications subject to change without notice.
- \* Some models may not be available for sales in certain countries.
- \* Model name can be varied by countries.

## Dryer

		Gas	
<b>CYLINDER</b>			
Drum Volume	cu.ft (l)	9.0 (254)	
Diameter	in.(mm)	28.2 (716)	
Depth	in.(mm)	24.2 (614)	
Capacity	lb (kg)	30 (13.6)	
<b>DIMENSIONS</b>			
Product (WxHxD)	in. (mm)	29 (737) x 40.2 (1,022) x 42.9 (1,090)	
With Door Opening	in. (mm)	65.1 (1,655)	
Carton (WxHxD)	in. (mm)	30.7 (781) x 44.7 (1,137) x 44.4 (1,128)	
Weight (Product/Carton)	lb (kg)	220 (100) / 240 (108.8)	
<b>OPERATION</b>			
Electric Requirements	V/Hz/amps	120/60/10	
Heating Type		Gas	
Type of Drying	W	Ventilation	
Air Flow	CFM	350	
Drum Motor	KW	0.5 (120V/60Hz)	
Fan Motor	KW	0.3	
Gas Ratings	KW/BTU	16.1 (EU) <sup>1)</sup> /55,000	
<b>CONNECTIONS</b>			
Air Outlet Diameter	in.(mm)	6 (154)	
Exhaust Airflow Diameter	in.(mm)	6 (154)	
<b>SYSTEM &amp; CONTROL</b>			
Pricing Program		Special Vended Price	
Intelligent Electronic Controls		0	
<b>PROGRAMS</b>			
Program List		High Temp	
		Med Temp	
		Low Temp	
		No Heat	
<b>EXTERNAL FINISH</b>			
Top Plate		Porcelain (Single) / Painted Steel (Stack)	
Transparent Glass Window Door		0	
Colors		Platinum	
Cabinet		Painted Steel	
Control Panel		Painted Steel	
Window Display		Silk Screen	
Window		Aluminium	

		Gas	
	Coin	Card / OPL	
Single	RN1870AN4	RN1870AH4	
Stack	RN1870AN2	RN1870AH2	

- \* Dimensions and weights are approximate.
- \* Design, features and specifications subject to change without notice.
- \* Some models may not be available for sales in certain countries.
- \* Model name can be varied by countries.
- \* Titan-C Dryer is stacked in the factory.
- 1) Gas rating is different by countries.

